



Fixed speed
Cooling & heating

MFR PORTABLE



Optimal comfort:
reversible solution

THE + «SUSTAINABLE DEVELOPMENT»

→ Environmentally friendly R290 fluid

THE + «USER»

→ Easy to move with its wheels and handles

→ Easy to read with its digital display

→ Remotely controllable with RC unit

THE + «TECHNOLOGY»

→ Sealing kit included

→ Evacuation of condensates by evaporation

+ PRODUCTS


- RC08C remote control included
- Compact & design
- Reversible product (cooling/heating)

FEATURES

AIR QUALITY/CLEAN:



USER FUNCTIONS:



INSTALLER FUNCTIONS:



MFR TECHNICAL DATA

Indoor unit		AW-MFR012-H41
Phase		Single phase
COOLING		
Rated power	kW	3,52
Rated power input	kW	1,357
Current	A	5,9
EER/Energy label		2,60/A
Operating limits	°C	17°/35° Dry bulb
HEATING		
Rated power	kW	2,93
Rated power input	kW	1,045
Current	A	5
COP/Energy label		2,8/A
Operating limits	°C	5°/30° Dry bulb
INDOOR UNIT		
Type		Monobloc
Sound pressure level to 1 m (LS/MS/HS)	dB(A)	54/54/55
Sound power Level	dB(A)	63
Airflow (LS/MS/HS)	m³/h	355/370/420
Diameter flexible emission duct	mm	150
Length range of heat emission duct	m	0,5-1,50
Dehumidification	l/h	1,8
Outline dimensions (WxHxD)	mm	467x765x397
Package dimensions (WxHxD)	mm	515x890x440
Net weight/Gross weight	kg	33/36,5
Part number		7MB021062
POWER SUPPLY		
Phase/Voltage/Frequency		1P/230V/50Hz
PIPE LINE		
Refrigerant/GWP		R290/20
Charge	kg	0.22

* Packing 8 pieces minimum

FP-MFR EN 0420 - AIRWELL RESIDENTIAL SAS - Specifications subject to change without notice. Pictures non contractual. Printed in U.E.

Airwell

10, RUE DU FORT DE SAINT CYR - 78180 MONTIGNY LE BRETONNEUX, FRANCE
TEL.: +33 (0)1 76 21 82 00 - www.airwell-res.com

AIR CONDITIONING & HEATING