

MULTI-SPLIT SYSTEM

INDOOR UNITS SPECIFICATION FOR MULTI COMBINATIONS

Wall Mounted

SRK-ZSX(-W,-WB,-WT,-S)



Item	Model	SRK20ZSX	SRK25ZSX	SRK35ZSX	SRK50ZSX	SRK60ZSX
Nominal cooling capacity	kW	2.0	2.5	3.5	5.0	6.0
Nominal heating capacity	kW	3.0	3.4	4.5	5.8	6.8
Sound power level	Cooling	dB(A)		53	55	58
	Heating	dB(A)		55[53]	56	58
Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	dB(A)		38 / 31 / 24 / 19	39 / 33 / 25 / 19	43 / 35 / 26 / 19
	Heating(Hi/Me/Lo/Ulo)	dB(A)		38 / 33[32] / 25 / 19	40 / 34 / 27 / 19	42[41] / 35 / 28 / 19
Air flow	Cooling(Hi/Me/Lo/Ulo)	m ³ /min		11.3 / 9.1 / 6.0 / 5.0	12.2 / 10.0 / 6.7 / 5.0	13.1 / 10.8 / 7.3 / 5.0
	Heating(Hi/Me/Lo/Ulo)	m ³ /min		12.2 / 10.3 / 7.2 / 5.4	12.8 / 11.0 / 7.8 / 5.4	13.9 / 11.8 / 8.6 / 5.4
Exterior dimensions (H×W×D)	mm	305×920×220				
Net weight	kg	13.0				
Refrigerant piping size	Liquid / Gas	Φmm			6.35(1/4") / 9.52(3/8")	
Clean filter		Allergen Clear Filter ×1, Photocatalytic Washable Deodorizing Filter×1				

[] : in case of ZSX-S

Wall Mounted

SRK-ZR(-W,-S)



Item	Model	SRK71ZR		
Nominal cooling capacity	kW	7.1		
Nominal heating capacity	kW	8.0		
Sound power level	Cooling	dB(A)		57[58]
	Heating	dB(A)		60
Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	dB(A)		44 / 41 / 37 / 25
	Heating(Hi/Me/Lo/Ulo)	dB(A)		46 / 39 / 35 / 28
Air flow	Cooling(Hi/Me/Lo/Ulo)	m ³ /min		20.5 / 18.6 / 16.2 / 10.4
	Heating(Hi/Me/Lo/Ulo)	m ³ /min		25.0[25.5] / 19.8 / 17.3 / 13.3
Exterior dimensions (H×W×D)	mm	339×1197×262		
Net weight	kg	15.5		
Refrigerant piping size	Liquid / Gas	Φmm		6.35 (1/4") / 15.88 (5/8")
Clean filter		Allergen Clear Filter ×1, Photocatalytic Washable Deodorizing Filter×1		

[] : in case of ZR-S

Wall Mounted

SRK-ZS(-W,-WB,-WT,-S,-SB,-ST)



Item	Model	SRK20ZS	SRK25ZS	SRK35ZS	SRK50ZS
Nominal cooling capacity	kW	2.0	2.5	3.5	5.0
Nominal heating capacity	kW	3.0	3.4	4.5	5.8
Sound power level	Cooling	dB(A)		48[50]	50[52]
	Heating	dB(A)		50[52]	53[55]
Sound pressure level	Cooling(Hi/Me/Lo/Ulo)	dB(A)		34 / 25 / 22 / 19	36 / 28 / 23 / 19
	Heating(Hi/Me/Lo/Ulo)	dB(A)		36 / 29 / 23 / 19	39 / 30 / 24 / 19
Air flow	Cooling(Hi/Me/Lo/Ulo)	m ³ /min		9.3 / 7.0 / 5.9 / 5.0	9.9 / 8.0 / 5.9 / 5.0
	Heating(Hi/Me/Lo/Ulo)	m ³ /min		10.0 / 8.5 / 6.5 / 5.9	11.3 / 8.7 / 6.7 / 5.9
Exterior dimensions (H×W×D)	mm	290×870×230			
Net weight	kg	9.5			
Refrigerant piping size	Liquid / Gas	Φmm			6.35(1/4") / 9.52(3/8")
Clean filter		Allergen Clear Filter × 1, Photocatalytic Washable Deodorizing Filter × 1			

[] : in case of ZS-S,-SB,-ST

Wall Mounted

SKM-ZSP



Item	Model	SKM20ZSP-S	SKM25ZSP-S	SKM35ZSP-S	
Nominal cooling capacity	kW	2.0	2.5	3.5	
Nominal heating capacity	kW	3.0	3.4	4.5	
Sound power level	Cooling	dB(A)		58	
	Heating	dB(A)		56	
Sound pressure level	Cooling(Hi/Me/Lo)	dB(A)		42 / 35 / 24	
	Heating(Hi/Me/Lo)	dB(A)		41 / 35 / 27	
Air flow	Cooling(Hi/Me/Lo)	m ³ /min		8.5 / 7.0 / 5.0	
	Heating(Hi/Me/Lo)	m ³ /min		8.0 / 7.0 / 5.5	
Exterior dimensions (H×W×D)	mm	262×769×210			
Net weight	kg	7.6			
Refrigerant piping size	Liquid / Gas	Φmm			6.35(1/4")/9.52(3/8")
Clean filter		—			